APart CMRQ108

IN SPEAKER



Multiroom, hi-end stereo enjoyment and 5.1 sensations in the home environment or ultra-discrete background music in a lounge, a bar, boutique,...: Style and quality meet in the CMRQ Kevlar [™] speaker. These in-wall / in-ceiling speakers bring crystal clear high notes and powerful deep basses that will astound the most demanding audience.

The CMRQ series has a 6.5" bass mid-speaker with a DuPont® Kevlar[™] cone and low loss rubber surround. High frequencies are covered by a tiltable 1" silk dome tweeter that is carefully matched to deliver an amazing and detailed sound, without the harshness commonly found in cheap metal alloy domes. The treble contour can be adjusted in 3 steps to suit your personal preferences.

CMRQ108 is 8-Ohm standard, and can easily be switched to 12 ohms. This way you can use two speakers in parallel on one amplifier channel, giving a total load impedance of 6 Ohm. This load impedance is standard for most surround receivers.

Mounting is easy and straightforward: the speaker clamps accept a wall thickness up to 28mm.

The CMRQ speakers are not magnetically shielded, which is not necessary unless you install them close CRT screen. Flatscreens, the ideal partners for CMRQ speakers are insensitive to magnetic fields. Instead, APart has paid attention to many other details: gold plated wire terminals, a carefully tuned crossover with high quality components, solid steel speaker grille and top notch quality are your guarantee for the purest musical enjoyment.



TECHNICAL SPECIFICATIONS

Speaker type Bass-mid speaker Tweeter

Nominal impedance Recommended amplifier power Tweeter level adjustment Crossover frequency and slope Frequency range Sensitivity Dimensions outside H x W Cutout dimensions H x W x D Accessories supplied

in-wall/in-ceiling, two way hifi. 6.5' DuPont® Kevlar cone 1' soft dome, pivotable within approx 25 degrees in all directions 8 ohms (can be switched to 12 ohms) 15 to 120 watts per channel 3 level treble contour switch 3000 Hz, 12 dB/oct 45* - 25000 Hz 87 dB spl (2.83V/1m) 296 x 196 mm 272 x 172 x 78 mm grille removal tool, build-in template Can be painted into any RAL color from a minimum of 12 pieces - Ref.: PAINTCM

INFO@APART-AUDIO.COM WWW.APART-AUDIO.COM